Municipal Stormwater System Inventory & Data Collection

City of Greensboro, NC



INVENTORY 101

Presented by:



Erosion & Sediment Control Design Seminar Sponsored by NC DENR Land Quality

> New Bern, NC February 8, 2000

Dewberry & Davis

Presentation Outline

- Goals of the Inventory
- Project History
- Project Description
- Innovative Field Procedures
- Problems / Pitfalls
- Future Uses of the Data

Inventory Goals

- Establish location, condition, size and system connectivity of infrastructure and conveyance system.
- Comply with NPDES Stormwater Permit.
- Use data for proactive planning, maintenance, work order requests.
- Identification of illicit discharges & tracking spills
- Further identification of flooding / water quality problem areas
- Link the GIS inventory data with modeling software for Watershed Master Plans.


Presentation Outline

- Goals of the Inventory
- Project History
- Project Description
- Innovative Field Procedures
- Problems / Pitfalls
- Future Uses of the Data


Project History


- Phase I: Pilot Basin Inventory
- Phase II: North & South Buffalo Creek
 Sub-Watersheds 1 & 2
- Phase III: Citywide Inventory


NORTH CAROLINA RIVER BASINS





Map Prepared by the N.C. Geographic Information & Analysis *115 Hillsborough Street * Raleigh, NC 27609 * (919)733-2090











By The Numbers...

	Project Phase			
Feature Type	Pilot	Phase II	Phase III	Totals
Inlets / Manholes	2,366	16,838	14,584	33,788
Pipes	2,187	17,665	13,922	33,774
Culverts	64	219	248	531
Bridges	1	30	25	56
Lakes	5	36	32	73
Channels	177	1,100	1,350	2,627
Digital Pictures	-	3,200	16,366	19,566
Cross Sections Surveyed	-	275	331	606
Totals	4,800	39,363	46,858	91,021

Data as of February 2, 2000

Presentation Outline


- Goals of the Inventory
- Project History
- Project Description
- Innovative Field Procedures
- Problems / Pitfalls
- Future Uses of the Data

Project Description

- Developed GIS / Database Design
- Determined Scope / Accuracy Standards
 - Pipes larger than 12"
 - City / DOT and and Private Maintained Systems
 - Location Accuracy to +/- 5 cm
 - No Driveway Pipes
- Developed Quality Assurance Plan
- Established GPS Base Station Control Network
- Feature Attribution
- Feature Location GPS and Traditional Survey Methods
- Quality Control
- GIS Data Integration
- Final Deliverable ARC/INFO Coverage

Feature Attribution

- Pen-based Field Computers
- Attributes Collected
 - Structure Size
 - Pipe Diameters
 - Material
 - Condition
 - System Connectivity(Channels & Swales)
 - Odors or Illicit Connections?
- Bridge / Culverts / Dams Attributed
- Digital Pictures




GPS Location Surveys


- GPS = Global Positioning Systems
- Accuracy: +/- 5 cm
- Approximately 50-70% of Points Are "GPS-able"
- 2 Person Field Crews Begin at Outfalls and Work Upstream
- Unique Identification Numbers
- Crews Trace System Connectivity
- Field Sketches of System





What Is Complete System Connectivity?














Structure Condition Assessment




System Outfall Inventory





Illicit Discharges Are Identified By Field Crews - City notified as soon as possible


Open Channel Inventory




Field → GIS → H&H Modeling



Data is collected to easily import and link the GIS Inventory into standard hydraulic models (HEC-RAS)





Presentation Outline

- Goals of the Inventory
- Project History
- Project Description
- Innovative Field Procedures
- Problems / Pitfalls
- Future Uses of the Data

Innovative Field Procedures

- Pen Computers
- Custom Data Collection Software
- Custom Laser Measurement Device
- Quality Control
- Advanced Digital Camera Techniques
- Experienced and Properly Trained Field Crews

Pen Computers

- State-of-the-art pen computers
- Bring the GIS "...from the desktop to the street corner..."
- Eliminate Paper Field Notes
- Ruggedized / Waterproof for Extreme Conditions
- Interface with GPS Receivers







Data Collection Software

- Written in MapObjects / Visual Basic
- Data is Collected directly in GIS Format
- Custom Built for Stormwater Inventory
- "Wizard-Type" Dialog Boxes Guide Field Crews
- "On-the-fly" Quality Control Checks


"Wizard" Type Dialog Boxes



"On-the-fly" Quality Control Checks



Custom Laser Device - Plan



Custom Laser Device - In Use






Pipe Inverts are measured to an accuracy of +/- 0.1'

Quality Control

- "Independent" QC Crew Checks
- Check a Minimum of 5% of Features
 - Pipe Diameters
 - Pipe / Structure Inverts
 - Pipe / Structure Material
 - System Connectivity
 - Structure Conditions
- Statistical Analysis of Data
- Confidence Interval Testing

Quality Control

- Statistical Analysis of Data
- Confidence Interval Testing



The People Make the Project

- City and Consultant work together in Partnership
- Crew Leaders are Engineers or GIS Specialists
- 100+ Page Field Inventory Procedures Manual
- 2 weeks Office/Field training

Presentation Outline

- Goals of the Inventory
- Project History
- Project Description
- Innovative Field Procedures
- Problems / Pitfalls
- Future Uses of the Data

Problems / Pitfalls

- RTK GPS vs. Trees and Buildings
- Suggest relative high accuracy for vertical data; less may be OK for horizontal
- Inaccessible Structures
 Know when to say when!
- Keep your inventory data current Don't make this only a "snapshot"
- Subjective Condition Ratings training and consistency in the field is the key
- Process Data as you go!

What Can You Do With The Data?

